

160 W LED 80 x 80 cm coverage

Key Features

Extended Spectrum

As in the previous generation, we of course rely on a full spectrum (385 to 730 nm) expanded to include UV light and Far Red in the seriesX PWR. You can look forward to higher active ingredient and terpene contents as well as significantly higher photosynthesis rates.

Clever Lighting

The Series-X PWR models are based on the most popular square tent sizes. This way you can easily find the right variant and ensure the ideal light supply for your plants.

Smart Install®

The newly developed suspension system gives you a wide variety of options for hanging the lamps. Thanks to the Smart Install[®] rail, the lamps (and also the light strips that can be separated from the driver box) can be attached directly to the ceiling. With air circulation, a distance of 2 cm between the heat sink and the ceiling is enough.

With Smart Install[®] you gain a high degree of flexibility in horticultural decisions and especially in height.

2-Channel-Dimming

With the new plant LEDs from the seriesX PWR, it is finally possible to individually dim two different light spectrums. With the help of our 2 channels (growth and flowering spectrum), you can individually adapt the plant light to the current needs of your plants and at the same time save a lot of electricity: While conventional plant LEDs are inevitably hung higher, our new models can simply be dimmed down.

This saves around 30% on electricity costs!


Core Data

| Number of LED Bars | 2 |
|--------------------------|------------------------|
| Product Weight | 3,8 kg |
| Dimensions (LxWxH) | 400 x 400 x 110 mm |
| LED-Bar (LxWxH) | 400 x 90 x 35 mm |
| Housing Material | Aluminum |
| Colour | Gray |
| Thermal Management | Passive |
| IP Rating | IP 65 |
| Max. Ambient Temperature | -5°C - 40°C |
| Certifications | CE/RoHS, UL 8800 ready |
| Warranty | 3 Years |
| | |

Performance Details

| AC Input Power | 160 W |
|--------------------|--------------------------------|
| Veg | 80 W |
| Flower | 160 W |
| Light Output (PPF) | 472 µmol/s |
| Efficacy | 2,95 µmol/J |
| Spectral Range | ca. 385 - 730 nm |
| Dimming | 0-100% continuously |
| | via rotary knobs |
| Beam Angle | 120° |
| AC Input Voltage | 100 - 277 V (AC) |
| Nominal AC Input | 120 V - 1 A / 208 V - 0,58 A |
| | 240 V - 0,5 A / 277 V - 0,43 A |
| Lifetime | > 50.000 h |
| EAN | 4260627954520 |
| | |
| | |

PPFD-Plot





Data Sheet

Product Description


The GCx4 PWR is the smallest version of the seriesX PWR with a maximum power consumption of 160 W. This makes it ideal for areas up to 80 x 80 cm. The compact module has two dimming controls with which the intensity of growth and the flowering spectrum can be adjusted separately.

On the underside of the LED strips, highly efficient full-spectrum chips in combination with additional far-red and UV diodes ensure a spectrum that is optimally utilized by the plants and offers very good color rendering for examining the plants.

Thanks to the adjustable extended light spectrum and the continuously dimmable light intensity, the lamps are suitable for all phases of cultivation - from freshly germinated seeds to plants ready for harvest. Since passive cooling ensures silent operation, the new seriesX PWR is the perfect companion for use in living spaces.

Scope of Delivery

1x Driver box, 2x LED Bars with slide-in-connector, 1x Mounting kit, 1x Power cord with 1.5m cable (Plug: C13/CEE-7/7 EU-Schuko)




Contact Information


Greenception is a Bifröst Brand

Bifröst GmbH Olfener Str. 112 59348 Lüdinghausen Germany ➢ office@greenception.com
⊕ www.Greenception.com
[O] greenception.worldwide
§ ⑤ +4915165147325


Dimensions



Spectra



Flower



Full Power (Veg + Flower)

